

Safety Data Sheet in accordance with HSNO

Printing date 08.05.2023

Version number 8

Revision: 05.05.2023



1 Identification of the substance or mixture and of the supplier

- **Product identifier**
- **Trade name:** PATTERN RESIN LS Liquid
- **Relevant identified uses of the substance or mixture and uses advised against**
No further relevant information available.
- **Application of the substance / the mixture** Auxillary for dental technology
- **Details of the supplier of the safety data sheet**
Henry Schein Dental

243-249 Bush Road, Rosedale
Auckland 0632, NEW ZEALAND

Free Phone: 0800 808 855
- **Further information obtainable from:** Regulatory affairs
- **Emergency telephone number:** 0800 764 766 (National Poisons Centre)

2 Hazards identification

- **Classification of the substance or mixture**
Flam. Liq. 2 H225 Highly flammable liquid and vapour.
Skin Irrit. 2 H315 Causes skin irritation.
Eye Irrit. 2 H319 Causes serious eye irritation.
Skin Sens. 1 H317 May cause an allergic skin reaction.
STOT SE 3 H335 May cause respiratory irritation.
- **Label elements**
- **GHS label elements** The product is classified and labelled according to the Globally Harmonised System (GHS).
- **Exemptions**
The product, regulated as an invasive medical device by the Regulation (EC) 2017/745, is exempted from labelling requirements for substances and mixtures (according to the provision of the Art 1.5).
- **Hazard pictograms**

GHS02 GHS07
- **Signal word** Danger
- **Hazard-determining components of labelling:**
Methyl methacrylate
ethyl methacrylate
2-(2H-benzotriazol-2-yl)-p-cresol
Ethyleneglycol dimethacrylate
- **Hazard statements**
Highly flammable liquid and vapour.
Causes skin irritation.
Causes serious eye irritation.

(Contd. on page 2)

-NZ-

Safety Data Sheet in accordance with HSNO

Printing date 08.05.2023

Version number 8

Revision: 05.05.2023

Trade name: **PATTERN_RESIN_LS_Liquid**

(Contd. of page 1)

May cause an allergic skin reaction.

May cause respiratory irritation.

· **Precautionary statements**

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Wear protective gloves/protective clothing/eye protection/face protection/hearing protection.

IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do.

Continue rinsing.

Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations.

· **Other hazards**

· **Results of PBT and vPvB assessment**

· **PBT:** Not applicable.

· **vPvB:** Not applicable.

3 Composition/Information on ingredients

· **Chemical characterisation: Mixtures**

· **Description:**

Only substances required to be mentioned according to Annex II of regulation 1907/2006 are listed. Information on the other substances that may be present can be obtained upon request.

· **Dangerous components:**

CAS: 80-62-6 EINECS: 201-297-1	Methyl methacrylate Flam. Liq. 2, H225; Skin Irrit. 2, H315; Skin Sens. 1, H317; STOT SE 3, H335	50-<75%
CAS: 6976-93-8 EINECS: 230-241-9	2-Methoxyethyl methacrylate Skin Irrit. 2, H315; Eye Irrit. 2, H319	10-<25%
CAS: 97-63-2 EINECS: 202-597-5	ethyl methacrylate Flam. Liq. 2, H225; Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317; STOT SE 3, H335	5-<10%
CAS: 3077-12-1 EINECS: 221-359-1	2,2'-(4-methylphenyl)imino]bisethanol Acute Tox. 3, H301; Skin Irrit. 2, H315; Eye Irrit. 2, H319; STOT SE 3, H335	1-<2.5%
CAS: 97-90-5 EINECS: 202-617-2	Ethylene glycol dimethacrylate Skin Sens. 1, H317; STOT SE 3, H335; Flam. Liq. 4, H227	1-<2.5%
CAS: 2440-22-4 EINECS: 219-470-5	2-(2H-benzotriazol-2-yl)-p-cresol Acute Tox. 3, H311; Acute Tox. 3, H331; Skin Sens. 1, H317	1-<2.5%

· **Additional information:** For the wording of the listed hazard phrases refer to section 16.

4 First aid measures

· **General information:**

Immediately remove any clothing soiled by the product.

If symptoms persist consult doctor.

· **After inhalation:**

Supply fresh air. If required, provide artificial respiration. Keep patient warm. Consult doctor if symptoms persist.

Take affected persons into fresh air and keep quiet.

· **After skin contact:**

Immediately wash with water and soap and rinse thoroughly.

Seek medical treatment.

If skin irritation continues, consult a doctor.

(Contd. on page 3)

Safety Data Sheet in accordance with HSNO

Printing date 08.05.2023

Version number 8

Revision: 05.05.2023

Trade name: PATTERN_RESIN_LS_Liquid

(Contd. of page 2)

- **After eye contact:**
Protect unharmed eye.
Rinse opened eye for several minutes under running water. Then consult a doctor.
- **After swallowing:**
Rinse out mouth and then drink plenty of water.
If symptoms persist consult doctor.
- **Information for doctor:**
- **Most important symptoms and effects, both acute and delayed** Allergic reactions
- **Indication of any immediate medical attention and special treatment needed**
No further relevant information available.

5 Fire fighting measures

- **Suitable extinguishing agents:** CO₂, sand, extinguishing powder. Do not use water.
- **For safety reasons unsuitable extinguishing agents:** Water
- **Special hazards arising from the substance or mixture**
Formation of toxic gases is possible during heating or in case of fire.
No further relevant information available.
- **Protective equipment:** Wear self-contained respiratory protective device.
- **Additional information**
Dispose of fire debris and contaminated fire fighting water in accordance with official regulations.

6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures**
Remove persons from danger area.
Keep away from ignition sources.
Wear protective equipment. Keep unprotected persons away.
Avoid contact with the eyes and skin.
Wear protective clothing.
- **Environmental precautions:**
Do not allow product to reach sewage system or any water course.
Inform respective authorities in case of seepage into water course or sewage system.
Do not allow to penetrate the ground/soil.
In case of seepage into the ground inform responsible authorities.
Prevent seepage into sewage system, workpits and cellars.
- **Methods and material for containment and cleaning up:**
Ensure adequate ventilation.
Absorb liquid components with liquid-binding material.
Dispose of the material collected according to regulations.
- **Reference to other sections**
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.

7 Handling and storage

- **Handling:**
- **Precautions for safe handling**
Ensure good ventilation/exhaustion at the workplace.

(Contd. on page 4)

-NZ-

Safety Data Sheet in accordance with HSNO

Printing date 08.05.2023

Version number 8

Revision: 05.05.2023

Trade name: **PATTERN_RESIN_LS_Liquid**

(Contd. of page 3)

Prevent formation of aerosols.

Avoid contact with the eyes and skin.

- **Information about fire - and explosion protection:**

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

Do not spray onto a naked flame or any incandescent material.

- **Storage:**

- **Requirements to be met by storerooms and receptacles:**

Store in a cool location.

Store only in unopened original receptacles.

- **Information about storage in one common storage facility:** Store away from foodstuffs.

- **Further information about storage conditions:**

Keep container tightly sealed.

Store in cool, dry conditions in well sealed receptacles.

Protect from heat and direct sunlight.

Store in a cool place.

- **Specific end use(s)** No further relevant information available.

8 Exposure controls/personal protection

- **Additional information about design of technical facilities:** No further data; see section 7.

- **Ingredients with limit values that require monitoring at the workplace:**

80-62-6 Methyl methacrylate

WES (New Zealand)	Short-term value: 416 mg/m ³ , 100 ppm Long-term value: 208 mg/m ³ , 50 ppm skin, dsen
-------------------	--

IOELV (European Union)	Short-term value: 100 ppm Long-term value: 50 ppm
------------------------	--

- **DNELs**

Inhalative	DNEL inhalation	mg/m ³ (rat (f+m))
------------	-----------------	-------------------------------

80-62-6 Methyl methacrylate

Dermal	DNEL dermal	13.67 mg/kg bw/day (man) (worker, l. te., syst.)
--------	-------------	--

Inhalative	DNEL inhalation	208 mg/m ³ (air) (worker, l. te., syst.)
------------	-----------------	---

- **Additional information:** The lists valid during the making were used as basis.

- **Personal protective equipment:**

- **General protective and hygienic measures:**

The usual precautionary measures are to be adhered to when handling chemicals.

Avoid contact with the eyes and skin.

Wash hands before breaks and at the end of work.

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

- **Respiratory protection:**

In the event that the limit exposure is exceeded, use a respiratory protective device with filter A.

Suitable respiratory protective device recommended.

- **Protection of hands:**



Protective gloves

(Contd. on page 5)

Safety Data Sheet in accordance with HSNO

Printing date 08.05.2023

Version number 8

Revision: 05.05.2023

Trade name: PATTERN_RESIN_LS_Liquid

(Contd. of page 4)

- **Material of gloves**

e.g. KCL Butoject 897

Butyl rubber, BR

Recommended thickness of the material: ≥ 0.29 mm

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

- **Penetration time of glove material**

For the mixture of chemicals mentioned below the penetration time has to be at least 60 minutes (Permeation according to EN 16523-1:2015: Level 2).

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

- **Eye protection:**



Tightly sealed goggles

9 Physical and chemical properties

- **General Information**

- **Appearance:**

- **Form:**

Liquid

- **Colour:**

Clear

- **Odour:**

Characteristic

- **Odour threshold:**

Not determined.

- **pH-value:**

Not determined.

- **Change in condition**

- **Melting point/freezing point:**

Undetermined.

- **Initial boiling point and boiling range:**

100 °C

- **Flash point:**

10 °C

- **Flammability (solid, gas):**

Highly flammable.

- **Auto-ignition temperature:**

Undetermined.

- **Decomposition temperature:**

Not determined.

- **Ignition temperature:**

Product is not selfigniting.

- **Explosive properties:**

Product does not present an explosion hazard.

- **Explosion limits:**

- **Lower:**

2.1 Vol %

- **Upper:**

12.5 Vol %

- **Vapour pressure:**

Not determined.

- **Density at 20 °C:**

0.95 g/cm³

- **Relative density**

Not determined.

- **Vapour density**

Not determined.

- **Evaporation rate**

Not determined.

- **Solubility in / Miscibility with**

- **water:**

Fully miscible.

- **Partition coefficient: n-octanol/water:**

Not determined.

- **Viscosity:**

- **Dynamic:**

Not determined.

- **Kinematic:**

Not determined.

(Contd. on page 6)

Safety Data Sheet in accordance with HSNO

Printing date 08.05.2023

Version number 8

Revision: 05.05.2023

Trade name: PATTERN_RESIN_LS_Liquid

(Contd. of page 5)

- | | |
|----------------------------|--|
| · Solvent content: | |
| · VOC (EC) | 0.0 g/l |
| · Other information | No further relevant information available. |

10 Stability and reactivity

- **Reactivity** No further relevant information available.
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **Possibility of hazardous reactions** No dangerous reactions known.
- **Conditions to avoid** No further relevant information available.
- **Incompatible materials:** No further relevant information available.
- **Hazardous decomposition products:** No dangerous decomposition products known.

11 Toxicological information

- **Information on toxicological effects**
- **Acute toxicity** Based on available data, the classification criteria are not met.
- **LD/LC50 values relevant for classification:**
 ATEmix (Oral) = 5284 mg/kg
 ATEmix (dermal) > 4740 mg/kg
 ATEmix (inhal.) = 15 mg/l

80-62-6 Methyl methacrylate

Oral	LD50	6,000 mg/kg (rabbit)
Dermal	LD50	>5,000 mg/kg (rab)
Inhalative	LC50/4 h	29.8 mg/l (rat (f+m))

97-63-2 ethyl methacrylate

Oral	LD50	13,424 mg/kg (rat (f+m))
Inhalative	LC50/4 h	55 mg/l (rat (f+m))

97-90-5 Ethyleneglycol dimethacrylate

Oral	LD50	8,700 mg/kg (rat (f+m))
Dermal	LD50	>2,000 mg/kg (rat (f+m))

2440-22-4 2-(2H-benzotriazol-2-yl)-p-cresol

Oral	LD50	10,000 mg/kg (rat (f+m))
Inhalative	LC50/4 h	0.59 mg/l (rat (f+m))

- **Skin corrosion/irritation** Causes skin irritation.
- **Serious eye damage/irritation** Causes serious eye irritation.
- **Respiratory or skin sensitisation** May cause an allergic skin reaction.
- **Germ cell mutagenicity** Based on available data, the classification criteria are not met.
- **Carcinogenicity** Based on available data, the classification criteria are not met.
- **Reproductive toxicity** Based on available data, the classification criteria are not met.
- **STOT-single exposure** May cause respiratory irritation.
- **STOT-repeated exposure** Based on available data, the classification criteria are not met.
- **Aspiration hazard** Based on available data, the classification criteria are not met.
- **Additional toxicological information:**
- **Repeated dose toxicity** No further relevant information available.

(Contd. on page 7)

Safety Data Sheet in accordance with HSNO

Printing date 08.05.2023

Version number 8

Revision: 05.05.2023

Trade name: **PATTERN_RESIN_LS_Liquid**

(Contd. of page 6)

- **CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)**
No further relevant information available.


12 Ecological information

- **Toxicity**
- **Aquatic toxicity:** No further relevant information available.
- **Persistence and degradability** No further relevant information available.
- **Behaviour in environmental systems:**
- **Bioaccumulative potential** No further relevant information available.
- **Mobility in soil** No further relevant information available.
- **Additional ecological information:**
- **General notes:**
Water hazard class 3 (German Regulation) (Self-assessment): extremely hazardous for water
Do not allow product to reach ground water, water course or sewage system, even in small quantities.
Danger to drinking water if even extremely small quantities leak into the ground.
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **Other adverse effects** No further relevant information available.

13 Disposal considerations

- **Waste treatment methods**
- **Recommendation**
Must not be disposed together with household garbage. Do not allow product to reach sewage system.
- **Uncleaned packaging:**
- **Recommendation:** Disposal must be made according to official regulations.
- **Recommended cleansing agents:** Water, if necessary together with cleansing agents.

14 Transport information

- | | |
|-------------------------------------|---|
| · UN-Number | |
| · NZS, IMDG, IATA | UN1247 |
| · UN proper shipping name | |
| · NZS | 1247 METHYL METHACRYLATE MONOMER, STABILIZED |
| · IMDG, IATA | METHYL METHACRYLATE MONOMER, STABILIZED |
| · Transport hazard class(es) | |
| · NZS | |
| |  |
| · Class | 3 (F1) Flammable liquids. |

(Contd. on page 8)

-NZ-

Safety Data Sheet in accordance with HSNO


Printing date 08.05.2023

Version number 8

Revision: 05.05.2023

Trade name: PATTERN_RESIN_LS_Liquid

(Contd. of page 7)

· Label	3
· IMDG, IATA	
	
· Class	3 Flammable liquids.
· Label	3
· Packing group	II
· NZS, IMDG, IATA	II
· Environmental hazards:	
· Marine pollutant:	No
· Special precautions for user	Warning: Flammable liquids.
· Hazard identification number (Kemler code):	33
· EMS Number:	F-E,S-D
· Stowage Category	C
· Stowage Code	SW1 Protected from sources of heat. SW2 Clear of living quarters.
· Transport in bulk according to Annex II of Marpol and the IBC Code	Not applicable.
· Transport/Additional information:	
· NZS	
· Limited quantities (LQ)	1L
· Excepted quantities (EQ)	Code: E2 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml
· Transport category	2
· Tunnel restriction code	D/E
· IMDG	
· Limited quantities (LQ)	1L
· Excepted quantities (EQ)	Code: E2 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml
· UN "Model Regulation":	UN 1247 METHYL METHACRYLATE MONOMER, STABILIZED, 3, II

15 Regulatory information

· **Safety, health and environmental regulations/legislation specific for the substance or mixture**

· **New Zealand Inventory of Chemicals**

80-62-6	Methyl methacrylate
6976-93-8	2-Methoxyethyl methacrylate
97-63-2	ethyl methacrylate
3077-12-1	2,2'-[(4-methylphenyl)imino]bisethanol

(Contd. on page 9)

Safety Data Sheet in accordance with HSNO

Printing date 08.05.2023

Version number 8

Revision: 05.05.2023

Trade name: **PATTERN_RESIN_LS_Liquid**

(Contd. of page 8)

97-90-5	Ethyleneglycol dimethacrylate
2440-22-4	2-(2H-benzotriazol-2-yl)-p-cresol
128-37-0	Butylated hydroxytoluene

- **HSNO Approval numbers**

80-62-6	Methyl methacrylate	HSR001195
97-63-2	ethyl methacrylate	HSR001044

- **GHS label elements** The product is classified and labelled according to the Globally Harmonised System (GHS).

- **Hazard pictograms**



GHS02 GHS07

- **Signal word** Danger

- **Hazard-determining components of labelling:**

Methyl methacrylate

ethyl methacrylate

2-(2H-benzotriazol-2-yl)-p-cresol

Ethyleneglycol dimethacrylate

- **Hazard statements**

Highly flammable liquid and vapour.

Causes skin irritation.

Causes serious eye irritation.

May cause an allergic skin reaction.

May cause respiratory irritation.

- **Precautionary statements**

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Wear protective gloves/protective clothing/eye protection/face protection/hearing protection.

IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do.

Continue rinsing.

Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations.

- **Directive 2012/18/EU**

- **Named dangerous substances - ANNEX I** None of the ingredients is listed.

- **Seveso category** P5c FLAMMABLE LIQUIDS

- **Qualifying quantity (tonnes) for the application of lower-tier requirements** 5,000 t

- **Qualifying quantity (tonnes) for the application of upper-tier requirements** 50,000 t

- **Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

16 Other information

- **Relevant phrases**

H225 Highly flammable liquid and vapour.

H227 Combustible liquid.

H301 Toxic if swallowed.

H311 Toxic in contact with skin.

H315 Causes skin irritation.

(Contd. on page 10)

Safety Data Sheet in accordance with HSNO

Printing date 08.05.2023

Version number 8

Revision: 05.05.2023

Trade name: PATTERN_RESIN_LS_Liquid

(Contd. of page 9)

H317 May cause an allergic skin reaction.

H319 Causes serious eye irritation.

H331 Toxic if inhaled.

H335 May cause respiratory irritation.

· **Department issuing SDS:** Regulatory affairs

· **Contact:** msds@gc.dental

· **Abbreviations and acronyms:**

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOC: Volatile Organic Compounds (USA, EU)

DNEL: Derived No-Effect Level (REACH)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Flam. Liq. 2: Flammable liquids – Category 2

Flam. Liq. 4: Flammable liquids – Category 4

Acute Tox. 3: Acute toxicity – Category 3

Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Irrit. 2: Serious eye damage/eye irritation – Category 2

Skin Sens. 1: Skin sensitisation – Category 1

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

· **Sources**

• ECHA (<http://echa.europa.eu/>)

• EnviChem (www.echemportal.org)

· *** Data compared to the previous version altered.**

This version replaces all previous versions.

Disclaimer:

The information contained herein is believed to be true and accurate. However, all statements, recommendations or suggestions are made without any guarantee, representation or warranty, express or implied, on our part. Therefore, no warranty is made or to be implied that the information set out in this document is accurate or complete, and we accordingly exclude all liability in connection with the use of this information or the products referred to herein. All such risks are assumed by the purchaser/user. The information contained herein is also subject to change without notice. For the avoidance of doubt, however, nothing in this document excludes or limits our liability for death or personal injury caused by our negligence or for fraudulent misrepresentation.