

Page 1/11

Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 18.06.2024

Version number 3 (replaces version 2)

Revision: 18.06.2024

SECTION 1: Identification of the substance/mixture and of the company/undertaking

- · 1.1 Product identifier
- · Trade name: GC Fuji COAT LC
- 1.2 Relevant identified uses of the substance or mixture and uses advised against No further relevant information available.

· Application of the substance / the mixture Auxiliary for dental technology

• 1.3 Details of the supplier of the safety data sheet • Manufacturer/Supplier:

GC EUROPE N.V. Interleuvenlaan 33 B-3001 Leuven Tel. +32/(0)16/74.10.00 Fax +32/(0)16/40.26.84 msds@gc.dental

· Information department: Regulatory affairs

· 1.4 Emergency telephone number: International: +01-813-248-0585 (ChemTel Inc.)

SECTION 2: Hazards identification

· 2.1 Classification of the substance or mixture

· Classification according to Regulation (EC) No 1272/2008

Flam. Liq. 2 H225 Highly flammable liquid and vapour.

Skin Irrit. 2 H315 Causes skin irritation.

Skin Sens. 1 H317 May cause an allergic skin reaction.

Repr. 2 H361f Suspected of damaging fertility (causing atrophy of the testes).

STOT SE 3 H335 May cause respiratory irritation.

· 2.2 Label elements

· Labelling according to Regulation (EC) No 1272/2008

The product is classified and labeled according to the CLP regulation.

· Exemptions

The product, regulated as an invasive medical device by the Regulation (EC) 2017/745, is exempted from labelling requirements for substances and mixtures (according to the provision of the Art 1.5). • Hazard pictograms



· Signal word Danger

· Hazard-determining components of labeling:

Methyl methacrylate diphenyl(2,4,6-trimethylbenzoyl)phosphine oxide

- · Hazard statements
- H225 Highly flammable liquid and vapour.
- H315 Causes skin irritation.

(Contd. on page 2)

⁻ EU

Revision: 18.06.2024

Printing date 18.06.2024

Version number 3 (replaces version 2)

Trade name: GC_Fuji_COAT_LC

	(Contd. of page 1)
H317 May cause	e an allergic skin reaction.
H361f Suspected	of damaging fertility (causing atrophy of the testes).
H335 May cause	e respiratory irritation.
· Precautionary st	atements
P210	Keep away from heat/sparks/open flames/hot surfaces No smoking.
P280	Wear protective gloves/protective clothing/eye protection/face protection.
P303+P361+P3	53 If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/
	shower.
P308+P313	IF exposed or concerned: Get medical advice/attention.
P321	Specific treatment (see on this label).
P362+P364	Take off contaminated clothing and wash it before reuse.
P405	Store locked up.
P501	Dispose of contents/container in accordance with local/regional/national/international
	regulations.
· 2 3 Other hazard	le l

2.3 Other hazards

- · Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · vPvB: Not applicable.

SECTION 3: Composition/information on ingredients

· 3.2 Chemical characterization: Mixtures

· Description:

Only substances required to be mentioned according to Annex II of regulation 1907/2006 are listed. Information on the other substances that may be present can be obtained upon request.

· Dangerous components:		
		25-<50%
	Flam. Liq. 2, H225; Skin Irrit. 2, H315; Skin Sens. 1, H317; STOT SE 3, H335	
75980-60-8	diphenyl(2,4,6-trimethylbenzoyl)phosphine oxide	≥3-<5%
	Repr. 2, H361f	
· SVHC		

SVHC

75980-60-8 diphenyl(2,4,6-trimethylbenzoyl)phosphine oxide

• Additional information: For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

• 4.1 Description of first aid measures

· General information:

Immediately remove any clothing soiled by the product.

If symptoms persist consult doctor.

• After inhalation:

Supply fresh air. If required, provide artificial respiration. Keep patient warm. Consult doctor if symptoms persist. Take affected persons into fresh air and keep quiet.

• After skin contact:

Immediately wash with water and soap and rinse thoroughly.

Seek medical treatment.

If skin irritation continues, consult a doctor.

· After eye contact:

Rinse opened eve for several minutes under running water.

(Contd. on page 3)

Printing date 18.06.2024

Version number 3 (replaces version 2)

Revision: 18.06.2024

(Contd. of page 2)

Trade name: GC_Fuji_COAT_LC

If symptoms persist consult doctor.

• After swallowing:

Rinse out mouth and then drink plenty of water. If symptoms persist consult doctor.

• 4.2 Most important symptoms and effects, both acute and delayed Allergic reactions

• 4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

SECTION 5: Firefighting measures

- 5.1 Extinguishing media
- Suitable extinguishing agents: CO2, sand, extinguishing powder. Do not use water.
- · For safety reasons unsuitable extinguishing agents: Water
- 5.2 Special hazards arising from the substance or mixture Formation of toxic gases is possible during heating or in case of fire. No further relevant information available.
- 5.3 Advice for firefighters
- · Protective equipment: Wear self-contained respiratory protective device.
- · Additional information

Dispose of fire debris and contaminated fire fighting water in accordance with official regulations.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures Remove persons from danger area.
Keep away from ignition sources Avoid contact with the eyes and skin.
Wear protective clothing.
6.2 Environmental precautions: Do not allow product to reach sewage system or any water course.
Inform respective authorities in case of seepage into water course or sewage system. Do not allow to penetrate the ground/soil.
In case of seepage into the ground inform responsible authorities.
6.3 Methods and material for containment and cleaning up:

Ensure adequate ventilation.

Absorb liquid components with liquid-binding material.

Dispose of the collected material according to regulations.

6.4 Reference to other sections
 See Section 7 for information on safe handling.
 See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage

· 7.1 Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace. Prevent formation of aerosols. Avoid contact with the eyes and skin.

• Information about protection against explosions and fires: Keep ignition sources away - Do not smoke.

(Contd. on page 4)

Printing date 18.06.2024

Version number 3 (replaces version 2)

Revision: 18.06.2024

(Contd. of page 3)

Trade name: GC_Fuji_COAT_LC

Protect against electrostatic charges. Do not spray on a naked flame or any incandescent material.

• 7.2 Conditions for safe storage, including any incompatibilities

• Storage:

• **Requirements to be met by storerooms and receptacles:** Store in a cool location. Store only in unopened original receptacles.

• Information about storage in one common storage facility: Store away from foodstuffs.

• Further information about storage conditions: Keep receptacle tightly sealed.

Store in cool, dry conditions in well sealed receptacles.

Protect from heat and direct sunlight.

Store in a cool place.

• 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

· 8.1 Control parameters

· Components with limit values that require monitoring at the workplace:

80-62-6 Methyl methacrylate

IOELV Short-term value: 100 ppm

Long-term value: 50 ppm

· DNELs

80-62-6 Methyl methacrylate

Dermal DNEL dermal 13.67 mg/kg bw/day (man) (worker, l. te., syst.)

Inhalative DNEL inhalation 208 mg/m3 (air) (worker, l. te., syst.)

• Additional information: The lists that were valid during the creation were used as basis.

· 8.2 Exposure controls

• Additional information about design of technical systems: No further data; see section 7.

- Personal protective equipment:
- General protective and hygienic measures:

The usual precautionary measures for handling chemicals should be followed.

Avoid contact with the eyes and skin.

Wash hands before breaks and at the end of work.

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

· Breathing equipment: Suitable respiratory protective device recommended.

· Protection of hands:



Protective gloves

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

(Contd. on page 5)

⁻ EU

EU -

Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 18.06.2024

*

Version number 3 (replaces version 2)

Revision: 18.06.2024

Trade name: GC_Fuji_COAT_LC

Eye protection:	(Contd. of page
Tightly sealed goggles	
SECTION 9: Physical and chemical pr	roperties
9.1 Information on basic physical and chemica	l properties
General Information	
Physical state	Fluid
Color:	Light yellow
Odor:	Ester-like
Odor threshold:	Not determined.
Melting point/Melting range:	Undetermined.
Boiling point/Boiling range:	100.8 °C
Flammability (solid, gaseous): Explosion limits:	Highly flammable.
Lower:	2.1 Vol % (80-62-6 Methyl methacrylate)
Upper:	12.5 Vol % (80-62-6 Methyl methacrylate)
Flash point:	11 °C
Auto igniting:	Undetermined.
Decomposition temperature:	Not determined.
pH-value:	Not determined.
Viscosity:	
Kinematic:	Not determined.
Dynamic:	Not determined.
Solubility in / Miscibility with	
Water:	Insoluble.
Partition coefficient (n-octanol/water):	Not determined.
Vapor pressure:	Not determined.
Density and/or relative density	
Density:	Not determined.
Relative density	Not determined.
Vapor density	Not determined.
9.2 Other information	
Appearance:	
Form:	Fluid
Important information on protection of hea	
environment, and on safety.	
Ignition temperature:	Product is not selfigniting.
Danger of explosion:	Product does not present an explosion hazard.
Solvent content:	1 rounci noes noi present un explosion nuzulu.
	$0.0 \alpha/l$
VOC (EC)	0.0 g/l
Change in condition	Not determined
Evaporation rate	Not determined.
Information with regard to physical hazard cla	sses
Explosives	Void
Flammable gases	Void
Aerosols	Void

Printing date 18.06.2024

Version number 3 (replaces version 2)

Revision: 18.06.2024

Trade name: GC_Fuji_COAT_LC

		(Contd. of page 5
Oxidising gases	Void	
Gases under pressure	Void	
Flammable liquids	Highly flammable liquid and vapour.	
Flammable solids	Void	
Self-reactive substances and mixtures	Void	
Pyrophoric liquids	Void	
Pyrophoric solids	Void	
Self-heating substances and mixtures	Void	
Substances and mixtures, which emit flammal	ble gases	
in contact with water	Void	
Oxidising liquids	Void	
Oxidising solids	Void	
Organic peroxides	Void	
Corrosive to metals	Void	
Desensitised explosives	Void	

SECTION 10: Stability and reactivity

· 10.1 Reactivity No further relevant information available.

10.2 Chemical stability

• Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.

• 10.3 Possibility of hazardous reactions No dangerous reactions known.

• 10.4 Conditions to avoid No further relevant information available.

- 10.5 Incompatible materials: No further relevant information available.
- 10.6 Hazardous decomposition products: No dangerous decomposition products known.

SECTION 11: Toxicological information

• 11.1 Information on toxicological effects

• Acute toxicity: Based on available data, the classification criteria are not met.

· LD/LC50 values that are relevant for classification:

80-62-6 Methyl methacrylate

	-	-
Oral	LD50	6,000 mg/kg (rabbit)
Dermal	LD50	>5,000 mg/kg (rab)
Inhalative	LC50/4 h	29.8 mg/l (rat (f+m))

• on the skin: Causes skin irritation.

• on the eye: Based on available data, the classification criteria are not met.

• Sensitization: May cause an allergic skin reaction.

• Germ cell mutagenicity Based on available data, the classification criteria are not met.

• Carcinogenicity Based on available data, the classification criteria are not met.

• *Reproductive toxicity Suspected of damaging fertility (causing atrophy of the testes).*

• Specific target organ toxicity - single exposure May cause respiratory irritation.

• Specific target organ toxicity - repeated exposure Based on available data, the classification criteria are not met.

• Aspiration hazard Based on available data, the classification criteria are not met.

• Additional toxicological information:

· OSHA-Ca (Occupational Safety & Health Administration)

None of the ingredients is listed.

• *Repeated dose toxicity No further relevant information available.*

(Contd. on page 7)

EU

Printing date 18.06.2024

Version number 3 (replaces version 2)

Revision: 18.06.2024

Trade name: GC_Fuji_COAT_LC

• CMR effects (carcinogenity, mutagenicity and toxicity for reproduction) No further relevant information available. • 11.2 Information on other hazards	(Contd. of page 6)
· Endocrine disrupting properties	
128-37-0 Butylated hydroxytoluene	List II

SECTION 12: Ecological information

· 12.1 Toxicity

- · Aquatic toxicity: No further relevant information available.
- · 12.2 Persistence and degradability No further relevant information available.
- 12.3 Bioaccumulative potential No further relevant information available.
- · 12.4 Mobility in soil No further relevant information available.
- · 12.5 Results of PBT and vPvB assessment
- **PBT:** Not applicable.
- vPvB: Not applicable.
- 12.6 Endocrine disrupting properties For information on endocrine disrupting properties see section 11.
- · 12.7 Other adverse effects
- Additional ecological information:
- · General notes:

Water hazard class 3 (Self-assessment): extremely hazardous for water

Do not allow product to reach ground water, water course or sewage system, even in small quantities.

Danger to drinking water if even extremely small quantities leak into the ground.

SECTION 13: Disposal considerations

- · 13.1 Waste treatment methods
- · Recommendation:

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

· European waste catalogue	
	WASTES FROM HUMAN OR ANIMAL HEALTH CARE AND/OR RELATED RESEARCH (EXCEPT
	KITCHEN AND RESTAURANT WASTES NOT ARISING FROM IMMEDIATE HEALTH CARE)
18 01 00	wastes from natal care, diagnosis, treatment or prevention of disease in humans
18 01 06*	chemicals consisting of or containing hazardous substances

· Uncleaned packagings:

• Recommendation: Disposal must be made according to official regulations.

14.1 UN-Number	
ADR, IMDG, IATA	UN1247
14.2 UN proper shipping name	
DOT	Methyl methacrylate monomer, stabilized
ADR	1247 METHYL METHACRYLATE MONOMER, STABILIZED
IMDG, IATA	METHYL METHACRYLATE MONOMER, STABILIZED

Printing date 18.06.2024

Version number 3 (replaces version 2)

Revision: 18.06.2024

Trade name: GC_Fuji_COAT_LC

	(Contd. of page
14.3 Transport hazard class(es)	
ADR	
Class Label	3 (F1) Flammable liquids 3
IMDG, IATA	
Class	3 Flammable liquids
Label	3
14.4 Packing group	
ADR, IMDG, IATA	II
14.5 Environmental hazards: Marine pollutant:	No
14.6 Special precautions for user	Warning: Flammable liquids
Hazard identification number (Kemler code): EMS Number:	33 F-E,S-D
Stowage Category	С
Stowage Code	SW1 Protected from sources of heat. SW2 Clear of living quarters.
14.7 Transport in bulk according to Annex II	
MARPOL73/78 and the IBC Code	Not applicable.
Transport/Additional information:	<i>Temperature control is not required, in regards to Speci</i> <i>Provision 386. Product uses chemical stabilization.</i>
ADR	17
Limited quantities (LQ) Excepted quantities (EQ)	1L Code: E2
(22)	Maximum net quantity per inner packaging: 30 ml
T	Maximum net quantity per outer packaging: 500 ml
Transport category Tunnel restriction code	2 D/E
IMDG	
Limited quantities (LQ)	1L
Excepted quantities ($\widetilde{E}Q$)	Code: E2
	Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml
UN "Model Regulation":	UN 1247 METHYL METHACRYLATE MONOME. STABILIZED, 3, II

(Contd. on page 9)

Printing date 18.06.2024

Version number 3 (replaces version 2)

Revision: 18.06.2024

Trade name: GC_Fuji_COAT_LC

(Contd. of page 8)

E, NL

A4

A4

4

SECTION 15: Regulatory information

· 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture · Sara

• Section 355 (extremely hazardous substances):

None of the ingredient is listed.

• Section 313 (Specific toxic chemical listings):

80-62-6 Methyl methacrylate

· Proposition 65

· Chemicals known to cause cancer:

None of the ingredients is listed.

• Chemicals known to cause reproductive toxicity for females:

None of the ingredients is listed.

• Chemicals known to cause reproductive toxicity for males:

None of the ingredients is listed.

Chemicals known to cause developmental toxicity:

None of the ingredients is listed.

· Carcinogenic categories

· EPA (Environmental Protection Agency)

80-62-6 Methyl methacrylate

• TLV (Threshold Limit Value)

80-62-6 Methyl methacrylate

128-37-0 Butylated hydroxytoluene

· MAK (German Maximum Workplace Concentration)

128-37-0 Butylated hydroxytoluene

· NIOSH-Ca (National Institute for Occupational Safety and Health)

None of the ingredients is listed.

· Directive 2012/18/EU

• Named dangerous substances - ANNEX I None of the ingredients is listed.

· Seveso category P5c FLAMMABLE LIQUIDS

• Qualifying quantity (tonnes) for the application of lower-tier requirements 5,000 t

• Qualifying quantity (tonnes) for the application of upper-tier requirements 50,000 t

• **REGULATION (EC) No 1907/2006 ANNEX XVII** Conditions of restriction: 3

· DIRECTIVE 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment – Annex II

None of the ingredients is listed.

· REGULATION (EU) 2019/1148

Annex I - RESTRICTED EXPLOSIVES PRECURSORS (Upper limit value for the purpose of licensing under Article 5(3))

None of the ingredients is listed.

· Annex II - REPORTABLE EXPLOSIVES PRECURSORS

None of the ingredients is listed.

(Contd. on page 10)

Printing date 18.06.2024

Version number 3 (replaces version 2)

Revision: 18.06.2024

(Contd. of page 9)

Trade name: GC_Fuji_COAT_LC

· Regulation (EC) No 273/2004 on drug precursors

None of the ingredients is listed.

Regulation (EC) No 111/2005 laying down rules for the monitoring of trade between the Community and third countries in drug precursors

None of the ingredients is listed.

• REGULATION (EC) No 1005/2009 on substances that deplete the ozone layer – ANNEX I (Ozone- depleting potential)

• Other regulations, limitations and prohibitive regulations

· Substances of very high concern (SVHC) according to REACH, Article 57

75980-60-8 diphenyl(2,4,6-trimethylbenzoyl)phosphine oxide

• 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

· Relevant phrases

H225 Highly flammable liquid and vapour.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H335 May cause respiratory irritation.

H361f Suspected of damaging fertility.

· Classification according to Regulation (EC) No 1272/2008 Calculation method

· Department issuing SDS: Regulatory affairs

· Contact: msds@gc.dental

• Date of previous version 18.06.2024

• Version number of previous version: 2

• Abbreviations and acronyms:

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road) IMDG: International Maritime Code for Dangerous Goods

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOC: Volatile Organic Compounds (USA, EU)

DNEL: Derived No-Effect Level (REACH)

LC50: Lethal concentration, 50 percent LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

SVHC: Substances of Very High Concern

vPvB: very Persistent and very Bioaccumulative

NIOSH: National Institute for Occupational Safety

OSHA: Occupational Safety & Health Flam. Liq. 2: Flammable liquids – Category 2

Skin Irrit. 2: Skin corrosion/irritation – Category 2

Skin Sens. 1: Skin sensitisation – Category 1

Repr. 2: Reproductive toxicity – Category 2

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

Sources

• ECHA (http://echa.europa.eu/)

• EnviChem (www.echemportal.org)

(Contd. on page 11)

EU

Printing date 18.06.2024

Version number 3 (replaces version 2)

Revision: 18.06.2024

(Contd. of page 10)

EU

Trade name: GC_Fuji_COAT_LC

• * Data compared to the previous version altered.

This version replaces all previous versions.

Disclaimer:

The information contained herein is believed to be true and accurate. However, all statements, recommendations or suggestions are made without any guarantee, representation or warranty, express or implied, on our part. Therefore, no warranty is made or to be implied that the information set out in this document is accurate or complete, and we accordingly exclude all liability in connection with the use of this information or the products referred to herein. All such risks are assumed by the purchaser/user. The information contained herein is also subject to change without notice. For the avoidance of doubt, however, nothing in this document excludes or limits our liability for death or personal injury caused by our negligence or for fraudulent misrepresentation.