

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 15.05.2023

Version number 2 (replaces version 1)

Revision: 17.11.2022

SECTION 1: Identification of the substance/mixture and of the company/undertaking

- **1.1 Product identifier**
- **Trade name: GC RELINE II REMOVER FOR RESIN**
- **1.2 Relevant identified uses of the substance or mixture and uses advised against**
No further relevant information available.
- **Application of the substance / the mixture** Auxillary for dental technology
- **1.3 Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**
GC EUROPE N.V.
Interleuvenlaan 33
B-3001 Leuven
Tel. +32/(0)16/74.10.00
Fax +32/(0)16/40.26.84
msds@gc.dental
- **Further information obtainable from:** Regulatory affairs
- **1.4 Emergency telephone number:**
International: +01-813-248-0585 (ChemTel Inc.)
National poison center for United Kingdom of Great Britain and Northern Ireland:
Belfast: +44 28 90 63 2032
Birmingham: +44 121 507 4123
Edinburgh: +44 131 242 1383
Newcastle Upon Tyne: +44 191 2606182/+44 191 2606180
Penarth: +44 292 071 55 54

SECTION 2: Hazards identification

- **2.1 Classification of the substance or mixture**
- **Classification according to Regulation (EC) No 1272/2008**

| | |
|---------------------|--|
| Flam. Liq. 2 H225 | Highly flammable liquid and vapour. |
| Skin Irrit. 2 H315 | Causes skin irritation. |
| Eye Irrit. 2 H319 | Causes serious eye irritation. |
| Skin Sens. 1 H317 | May cause an allergic skin reaction. |
| STOT SE 3 H335-H336 | May cause respiratory irritation. May cause drowsiness or dizziness. |
- **2.2 Label elements**
- **Labelling according to Regulation (EC) No 1272/2008**
The product is classified and labelled according to the GB CLP regulation.
- **Exemptions**
The product, regulated as an invasive medical device by the Regulation (EC) 2017/745, is exempted from labelling requirements for substances and mixtures (according to the provision of the Art 1.5).
- **Hazard pictograms**



GHS02 GHS07

(Contd. on page 2)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 15.05.2023

Version number 2 (replaces version 1)

Revision: 17.11.2022

Trade name: GC_RELINE_II_REMOVER_FOR_RESIN

(Contd. of page 1)

· **Signal word** *Danger*· **Hazard-determining components of labelling:***Methyl methacrylate
ethyl acetate*· **Hazard statements***H225 Highly flammable liquid and vapour.**H315 Causes skin irritation.**H319 Causes serious eye irritation.**H317 May cause an allergic skin reaction.**H335-H336 May cause respiratory irritation. May cause drowsiness or dizziness.*· **Precautionary statements***P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.**P280 Wear protective gloves / eye protection / face protection.**P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].**P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.**P405 Store locked up.**P501 Dispose of contents/container in accordance with local/regional/national/international regulations.*· **2.3 Other hazards**· **Results of PBT and vPvB assessment**· **PBT:** Not applicable.· **vPvB:** Not applicable.

SECTION 3: Composition/information on ingredients

· **3.2 Mixtures**· **Description:***Only substances required to be mentioned according to Annex II of regulation 1907/2006 are listed. Information on the other substances that may be present can be obtained upon request.*· **Dangerous components:**

| | | |
|---|---|-------------------|
| <i>CAS: 141-78-6 EINECS: 205-500-4 Index number: 607-022-00-5</i> | <i>ethyl acetate Flam. Liq. 2, H225; Eye Irrit. 2, H319; STOT SE 3, H336, EUH066 substance with a Community workplace exposure limit</i> | <i>50-<75%</i> |
| <i>CAS: 80-62-6 EINECS: 201-297-1 Index number: 607-035-00-6</i> | <i>Methyl methacrylate Flam. Liq. 2, H225; Skin Irrit. 2, H315; Skin Sens. 1, H317; STOT SE 3, H335 substance with a Community workplace exposure limit</i> | <i>25-<50%</i> |

· **Additional information:** *For the wording of the listed hazard phrases refer to section 16.*

SECTION 4: First aid measures

· **4.1 Description of first aid measures**· **General information:***Immediately remove any clothing soiled by the product.**If symptoms persist consult doctor.*

(Contd. on page 3)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 15.05.2023

Version number 2 (replaces version 1)

Revision: 17.11.2022

Trade name: GC_RELINE_II_REMOVER_FOR_RESIN

(Contd. of page 2)

· After inhalation:

Supply fresh air. If required, provide artificial respiration. Keep patient warm. Consult doctor if symptoms persist. Take affected persons into fresh air and keep quiet.

· After skin contact:

Immediately wash with water and soap and rinse thoroughly.

Seek medical treatment.

If skin irritation continues, consult a doctor.

· After eye contact:

Protect unharmed eye.

Rinse opened eye for several minutes under running water. Then consult a doctor.

· After swallowing:

Rinse out mouth and then drink plenty of water.

If symptoms persist consult doctor.

· 4.2 Most important symptoms and effects, both acute and delayed Allergic reactions**· 4.3 Indication of any immediate medical attention and special treatment needed**

No further relevant information available.

SECTION 5: Firefighting measures

· 5.1 Extinguishing media

· Suitable extinguishing agents: CO₂, sand, extinguishing powder. Do not use water.

· For safety reasons unsuitable extinguishing agents: Water

· 5.2 Special hazards arising from the substance or mixture

Formation of toxic gases is possible during heating or in case of fire.

No further relevant information available.

· 5.3 Advice for firefighters

· Protective equipment: Wear self-contained respiratory protective device.

· Additional information

Dispose of fire debris and contaminated fire fighting water in accordance with official regulations.

SECTION 6: Accidental release measures

· 6.1 Personal precautions, protective equipment and emergency procedures

Remove persons from danger area.

Keep away from ignition sources.

Avoid contact with the eyes and skin.

Wear protective clothing.

· 6.2 Environmental precautions:

Do not allow product to reach sewage system or any water course.

Do not allow to penetrate the ground/soil.

· 6.3 Methods and material for containment and cleaning up:

Ensure adequate ventilation.

Absorb liquid components with liquid-binding material.

Dispose of the material collected according to regulations.

· 6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

GB

(Contd. on page 4)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 15.05.2023

Version number 2 (replaces version 1)

Revision: 17.11.2022

Trade name: GC_RELINE_II_REMOVER_FOR_RESIN

(Contd. of page 3)

SECTION 7: Handling and storage

- **7.1 Precautions for safe handling**
Ensure good ventilation/exhaustion at the workplace.
Prevent formation of aerosols.
Avoid contact with the eyes and skin.
- **Information about fire - and explosion protection:**
Keep ignition sources away - Do not smoke.
Protect against electrostatic charges.
Do not spray onto a naked flame or any incandescent material.
- **7.2 Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:**
Store in a cool location.
Store only in unopened original receptacles.
- **Information about storage in one common storage facility:** Store away from foodstuffs.
- **Further information about storage conditions:**
Keep container tightly sealed.
Store in cool, dry conditions in well sealed receptacles.
Protect from heat and direct sunlight.
Store in a cool place.
- **7.3 Specific end use(s)** No further relevant information available.

SECTION 8: Exposure controls/personal protection

- **8.1 Control parameters**

- **Ingredients with limit values that require monitoring at the workplace:**

141-78-6 ethyl acetate

| | |
|-----|--|
| WEL | Short-term value: 1468 mg/m ³ , 400 ppm |
| | Long-term value: 734 mg/m ³ , 200 ppm |

80-62-6 Methyl methacrylate

| | |
|-----|---|
| WEL | Short-term value: 416 mg/m ³ , 100 ppm |
| | Long-term value: 208 mg/m ³ , 50 ppm |

- **DNELs**

80-62-6 Methyl methacrylate

| | | |
|------------|-----------------|---|
| Dermal | DNEL dermal | 13.67 mg/kg bw/day (man) (worker, l. te., syst.) |
| Inhalative | DNEL inhalation | 208 mg/m ³ (air) (worker, l. te., syst.) |

- **Additional information:** The lists valid during the making were used as basis.

- **8.2 Exposure controls**

- **Appropriate engineering controls** No further data; see section 7.
- **Individual protection measures, such as personal protective equipment**
- **General protective and hygienic measures:**
The usual precautionary measures are to be adhered to when handling chemicals.
Avoid contact with the eyes and skin.
Wash hands before breaks and at the end of work.
Keep away from foodstuffs, beverages and feed.
Immediately remove all soiled and contaminated clothing
- **Respiratory protection:** Suitable respiratory protective device recommended.

(Contd. on page 5)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 15.05.2023

Version number 2 (replaces version 1)

Revision: 17.11.2022

Trade name: GC_RELINE_II_REMOVER_FOR_RESIN

(Contd. of page 4)

· **Hand protection**

Protective gloves

· **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· **Eye/face protection**

Tightly sealed goggles

SECTION 9: Physical and chemical properties

· **9.1 Information on basic physical and chemical properties**· **General Information**

| | |
|---|-------------------|
| · Physical state | Fluid |
| · Colour: | Clear |
| · Odour: | Fruit-like |
| · Odour threshold: | Not determined. |
| · Melting point/freezing point: | -83 °C |
| · Boiling point or initial boiling point and boiling range | Undetermined. |
| · Flammability | Highly flammable. |
| · Lower and upper explosion limit | |
| · Lower: | 2.1 Vol % |
| · Upper: | 12.5 Vol % |
| · Flash point: | -1 °C |
| · Auto-ignition temperature: | Undetermined. |
| · Decomposition temperature: | Not determined. |
| · pH | Not determined. |
| · Viscosity: | |
| · Kinematic viscosity | Not determined. |
| · Dynamic: | Not determined. |
| · Solubility | |
| · water: | Insoluble. |
| · Partition coefficient n-octanol/water (log value) | Not determined. |
| · Vapour pressure: | Not determined. |
| · Density and/or relative density | |
| · Density: | Not determined. |
| · Relative density | Not determined. |
| · Vapour density | Not determined. |

(Contd. on page 6)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 15.05.2023

Version number 2 (replaces version 1)

Revision: 17.11.2022

Trade name: GC_RELINE_II_REMOVER_FOR_RESIN

(Contd. of page 5)

- **9.2 Other information**
 - **Appearance:**
 - **Form:** Fluid
 - **Important information on protection of health and environment, and on safety.**
 - **Ignition temperature:** Product is not selfigniting.
 - **Explosive properties:** Product does not present an explosion hazard.
 - **Solvent content:**
 - **Organic solvents:** 70.0 %
 - **VOC (EC)** 700.0 g/l
 - **Change in condition**
 - **Evaporation rate** Not determined.
-
- **Information with regard to physical hazard classes**
 - **Explosives** Void
 - **Flammable gases** Void
 - **Aerosols** Void
 - **Oxidising gases** Void
 - **Gases under pressure** Void
 - **Flammable liquids** Highly flammable liquid and vapour.
 - **Flammable solids** Void
 - **Self-reactive substances and mixtures** Void
 - **Pyrophoric liquids** Void
 - **Pyrophoric solids** Void
 - **Self-heating substances and mixtures** Void
 - **Substances and mixtures, which emit flammable gases in contact with water** Void
 - **Oxidising liquids** Void
 - **Oxidising solids** Void
 - **Organic peroxides** Void
 - **Corrosive to metals** Void
 - **Desensitised explosives** Void

SECTION 10: Stability and reactivity

- **10.1 Reactivity** No further relevant information available.
- **10.2 Chemical stability**
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **10.3 Possibility of hazardous reactions** No dangerous reactions known.
- **10.4 Conditions to avoid** No further relevant information available.
- **10.5 Incompatible materials:** No further relevant information available.
- **10.6 Hazardous decomposition products:** No dangerous decomposition products known.

SECTION 11: Toxicological information

- **11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008**
- **Acute toxicity** Based on available data, the classification criteria are not met.

(Contd. on page 7)

GB

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 15.05.2023

Version number 2 (replaces version 1)

Revision: 17.11.2022

Trade name: GC_RELINER_II_REMOVER_FOR_RESIN

(Contd. of page 6)

· **LD/LC50 values relevant for classification:**

141-78-6 ethyl acetate

| | | |
|------------|----------|------------------------|
| Oral | LD50 | 4,935 mg/kg (rabbit) |
| Inhalative | LC50/4 h | 1,600 mg/l (rat (f+m)) |

80-62-6 Methyl methacrylate

| | | |
|------------|----------|-----------------------|
| Oral | LD50 | 6,000 mg/kg (rabbit) |
| Dermal | LD50 | >5,000 mg/kg (rab) |
| Inhalative | LC50/4 h | 29.8 mg/l (rat (f+m)) |

- **Skin corrosion/irritation** Causes skin irritation.
- **Serious eye damage/irritation** Causes serious eye irritation.
- **Respiratory or skin sensitisation** May cause an allergic skin reaction.
- **STOT-single exposure** May cause respiratory irritation. May cause drowsiness or dizziness.
- **Additional toxicological information:**
- **Repeated dose toxicity** No further relevant information available.
- **CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)**
No further relevant information available.
- **11.2 Information on other hazards**

· **Endocrine disrupting properties**

None of the ingredients is listed.

SECTION 12: Ecological information

- **12.1 Toxicity**
- **Aquatic toxicity:** No further relevant information available.
- **12.2 Persistence and degradability** No further relevant information available.
- **12.3 Bioaccumulative potential** No further relevant information available.
- **12.4 Mobility in soil** No further relevant information available.
- **12.5 Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **12.6 Endocrine disrupting properties**
The product does not contain substances with endocrine disrupting properties.
- **12.7 Other adverse effects**
- **Additional ecological information:**
- **General notes:**
Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water
Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

SECTION 13: Disposal considerations

- **13.1 Waste treatment methods**
- **Recommendation**
Must not be disposed together with household garbage. Do not allow product to reach sewage system.

(Contd. on page 8)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 15.05.2023

Version number 2 (replaces version 1)

Revision: 17.11.2022

Trade name: GC_RELINE_II_REMOVER_FOR_RESIN

(Contd. of page 7)

- **Uncleaned packaging:**
- **Recommendation:** Disposal must be made according to official regulations.

SECTION 14: Transport information

- **14.1 UN number or ID number**
- **ADR, IMDG, IATA**

UN1173

- **14.2 UN proper shipping name**
- **ADR**
- **IMDG, IATA**

1173 ETHYL ACETATE
ETHYL ACETATE

- **14.3 Transport hazard class(es)**
- **ADR**



- **Class**
- **Label**

3 (F1) Flammable liquids.
3

- **IMDG, IATA**



- **Class**
- **Label**

3 Flammable liquids.
3

- **14.4 Packing group**
- **ADR, IMDG, IATA**

II

- **14.5 Environmental hazards:**
- **Marine pollutant:**

No

- **14.6 Special precautions for user**
- **Hazard identification number (Kemler code):**
- **EMS Number:**
- **Stowage Category**

Warning: Flammable liquids.
33
F-E,S-D
B

- **14.7 Maritime transport in bulk according to IMO instruments**

Not applicable.

- **Transport/Additional information:**

- **ADR**
- **Limited quantities (LQ)**
- **Excepted quantities (EQ)**
- **Transport category**
- **Tunnel restriction code**

1L
Code: E2
Maximum net quantity per inner packaging: 30 ml
Maximum net quantity per outer packaging: 500 ml
2
D/E

(Contd. on page 9)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 15.05.2023

Version number 2 (replaces version 1)

Revision: 17.11.2022

Trade name: GC_RELINE_II_REMOVER_FOR_RESIN

(Contd. of page 8)

- | | |
|-----------------------------------|---|
| · IMDG | IL |
| · Limited quantities (LQ) | Code: E2 |
| · Excepted quantities (EQ) | Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml |
| · UN "Model Regulation": | UN 1173 ETHYL ACETATE, 3, II |

SECTION 15: Regulatory information

- **15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**
- **Directive 2012/18/EU**
- **Named dangerous substances - ANNEX I** None of the ingredients is listed.
- **Seveso category P5c FLAMMABLE LIQUIDS**
- **Qualifying quantity (tonnes) for the application of lower-tier requirements** 5,000 t
- **Qualifying quantity (tonnes) for the application of upper-tier requirements** 50,000 t
- **15.2 Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

- **Relevant phrases**
 - H225 Highly flammable liquid and vapour.
 - H315 Causes skin irritation.
 - H317 May cause an allergic skin reaction.
 - H319 Causes serious eye irritation.
 - H335 May cause respiratory irritation.
 - H336 May cause drowsiness or dizziness.
 - EUH066 Repeated exposure may cause skin dryness or cracking.
- **Classification according to Regulation (EC) No 1272/2008** Calculation method
- **Department issuing SDS:** Regulatory affairs
- **Contact:** msds@gc.dental
- **Abbreviations and acronyms:**
 - ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)
 - IMDG: International Maritime Code for Dangerous Goods
 - IATA: International Air Transport Association
 - GHS: Globally Harmonised System of Classification and Labelling of Chemicals
 - EINECS: European Inventory of Existing Commercial Chemical Substances
 - ELINCS: European List of Notified Chemical Substances
 - CAS: Chemical Abstracts Service (division of the American Chemical Society)
 - VOC: Volatile Organic Compounds (USA, EU)
 - DNEL: Derived No-Effect Level (UK REACH)
 - LC50: Lethal concentration, 50 percent
 - LD50: Lethal dose, 50 percent
 - PBT: Persistent, Bioaccumulative and Toxic
 - vPvB: very Persistent and very Bioaccumulative
 - Flam. Liq. 2: Flammable liquids – Category 2
 - Skin Irrit. 2: Skin corrosion/irritation – Category 2
 - Eye Irrit. 2: Serious eye damage/eye irritation – Category 2
 - Skin Sens. 1: Skin sensitisation – Category 1
 - STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

(Contd. on page 10)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 15.05.2023

Version number 2 (replaces version 1)

Revision: 17.11.2022

Trade name: GC_RELINE_II_REMOVER_FOR_RESIN

(Contd. of page 9)

Sources

- ECHA (<http://echa.europa.eu/>)
- EnviChem (www.echemportal.org)

*** Data compared to the previous version altered.**

This version replaces all previous versions.

Disclaimer:

The information contained herein is believed to be true and accurate. However, all statements, recommendations or suggestions are made without any guarantee, representation or warranty, express or implied, on our part. Therefore, no warranty is made or to be implied that the information set out in this document is accurate or complete, and we accordingly exclude all liability in connection with the use of this information or the products referred to herein. All such risks are assumed by the purchaser/user. The information contained herein is also subject to change without notice. For the avoidance of doubt, however, nothing in this document excludes or limits our liability for death or personal injury caused by our negligence or for fraudulent misrepresentation.